

Singer PR-48 Pressure Reducing Valve with Low Flow By-Pass

The 106-PR-48, and 206-PR-48 series Pressure Reducing Valves with low flow by-pass are based on the 106-PG, or 206-PG main valve. A direct acting pressure reducing valve is piped in parallel, using the main valve back port connections.



TECHNICAL GUIDE: **VH1.30**

Applications

Potable water
Municipal
Mining Applications
Irrigation Applications

Product Attributes

Maintains stable flow right down to zero
Precise and reliable pressure setting
By-pass piped in parallel to reduce space requirements

Approvals/Standards

AS 5081:2008
Flanges to AS/NZS 4087 Fig. B5
Coating complies with AS/NZS 4158

Quality

ISO 9001:2015 Quality Management Systems

The pilot valve senses the downstream pressure through a connection at the main valve outlet. Under flowing conditions, the pilot reacts to small changes in pressure to control the main valve position by modulating the pressure above the diaphragm. The downstream pressure is maintained virtually steady at the pilot set-point.

The by-pass valve is set 0.35 bar higher than the main valve. Under low flow conditions, the main PR valve closes and the by-pass stays open, controlling the pressure at very low flows without seat chatter. In typical pressure reducing applications, the standard port Model 206-PR-48 is often the best selection.




FIG. 1 Typical application

STANDARD MATERIALS

Standard materials for pilot system components are:

- ASTM B-62 bronze, or ASTM B-16 brass
- AISI 303 / 316 stainless-steel trim

SELECTION SUMMARY

1. Select the main PR valve series and size with sufficient capacity.

Note: Large Singer® valves (150 mm 106, 200 mm 206 & DN200 and up) have extremely precise control, even at low flows, making by-pass valves generally unnecessary for stable control, due to Single Rolling Diaphragm technology. Model PR-48 valves are usually required only for valve sizes with significant minimum flows. (80 mm to 200 mm 106, 100 mm to 250 mm 206).

2. If the outlet pressure is less than 35% of the inlet pressure, check for cavitation.
3. Ensure that the flange rating exceeds the maximum operating pressure.
4. Consider using a manual main by-pass line if necessary for service during maintenance periods.

ORDERING INSTRUCTIONS

Refer to the order form and ordering instructions.

Additionally, include the following information for this product:

1. Single chamber (106) or (206)
2. Outlet pressure range




FIG. 2 Schematic A-8063E

SCHEMATIC DRAWING

1. Main Valve - 106-PG or 206-PG
2. Isolation Valves - Standard 100 mm and Larger
3. Strainer - Standard 100 mm and Larger
4. Model 26 Flow Stabilizer / Opening Speed Control
5. Fixed Restriction
6. Isolation Valves - Standard 100 mm and Larger
7. Model 160 Pilot
Specify for:
 - 0.35 to 3.5 Bar
 - 0.70 to 5.5 Bar
 - 1.38 to 13.8 Bar
 - 6.9 to 20.7 Bar
8. Isolation Valve - Standard All Sizes
9. Direct Acting By-Pass - Range 2.07 – 10 Bar
10. Isolation Valve - Standard All Sizes

TABLE 1 106-PR-48 and 206-PR-48 Flow Capacity
(See 106-PG and 206-PG main valve section for other valve data)

Size (mm)	Minimum (L/s)		Maximum Continuous (L/s)	
	106-PR-48	206-PR-48	106-PR-48	206-PR-48
80	0	-	29	-
100	0	0	50	37
150	0	0	114	65
200	0	0	196	145
250	-	0	-	259



Scan for more
information

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hygrade Water product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hygrade Water unless expressly stated in any sale and purchase agreement entered into between Hygrade Water and the user.

January 2025

0800 494 723
hygradewater.co.nz

102 Neilson Street
Onehunga, Auckland 1061, New Zealand
PO Box 58 142, Botany, Auckland 2163

HW HYGRADE
WATER